



●时尚新潮的拼接设计

●娇小轻便易拿取

2807 二维扫码枪



1D / 2D



高速扫描



大视野



“超扫”解码



屏幕扫描



定制开发



运动容差

适用于多种应用场景



超市



商场



餐饮

性能优势：

- 低功耗、性能强大
- 全面读取所有主流一维、二维码
- 快速读取商品码和支付码
- 支持RS232接口和USB接口
- 精准识读破损码、污渍码、反光码等特殊条码
- 自感应识读，扫描灵敏

2807 技术规格书

物理参数		
尺寸		77.4mm x 69.3mm x 168.7mm
重量		132g
电压/电流		5 VDC +/-10% @ 500 mA
识读参数		
图像传感器		640 p(H) x 480 p(V)
光源		瞄准: 617nm 红色LED; 照明: 3500K 白色LED
视场角		40° (H) x 31° (V)
灵敏度		倾斜±65° 旋转360° 偏转±60°
打印对比度		≥25%
接口支持		USB, RS232
运动容差		>2m/s
识读码制	一维条码	Code 128, EAN-8, EAN-13, UPC-A, UPC-E, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code93, Codabar, GS1-128, MSI Plessey, Code 11, Code 32, CodaBlock F Code, GS1 DataBar, China Post, Telepen
	二维条码	PDF417, QR Code, Data Matrix, Aztec, Maxi Code, Hanxin
用户环境		
防护等级		IP52
工作温度		0° ~ 50° C
存储温度		-20° ~ 60° C
湿度		5% ~ 95%,无凝结
跌落高度		可承受多次1.5米高度正常跌落到水泥地面的冲击
环境光免疫		86,000 Lux.



典型码识读距离

Code 39 (3.13 mil)	50mm-100mm
Code 39 (5.13 mil)	30mm-170mm
Code 39 (20 mil)	30mm-450mm
UPC-A (13 mil)	30mm-320mm
PDF (6.88 mil)	30mm-180mm
DM (10 mil)	20mm-180mm
QR (20 mil)	20mm-300mm

Technical drawing of a hand-held sprayer nozzle assembly, showing multiple views and dimensions in millimeters (mm).

Dimensions:

- Top View (Left):**
 - Overall width: 77.4
 - Overall height: 69.3
 - Internal width: 36.5
 - Internal height: 53.00
 - Top hole diameter: $\Phi 7.50$
 - Bottom hole diameter: $\Phi 1.00$
- Front View (Top Left):**
 - Overall height: 168.7
 - Internal width: 38.7
- Front View (Top Middle):**
 - Internal width: 31.2
- Front View (Top Right):**
 - Overall width: 69.3
 - Overall height: 168.7
 - Base width: 78.2
- Front View (Bottom Left):**
 - Overall width: 78.2
 - Overall height: 78.6
 - Internal width: 38.0
 - Internal height: 42.2
 - Base width: 107.5
 - Base height: 9.50
- Front View (Bottom Middle):**
 - Overall width: 107.5
 - Overall height: 78.6
 - Internal width: 38.0
 - Internal height: 42.2
 - Base width: 107.5
 - Base height: 9.50
- Front View (Bottom Right):**
 - Overall width: 77.4
 - Overall height: 168.7
 - Base width: 107.5
 - Base height: 9.50
 - Internal width: 38.0
 - Internal height: 42.2
 - Base width: 107.5
 - Base height: 9.50